

Background of the Invention

1. Field of the Invention

5

The present invention relates generally to systems that provide for the shared-use of vehicles. More particularly, the invention relates to a system that allows one of a plurality of drivers to automatically make a reservation for a car, then the system controls the access and use of the car, and the return of the car, including billing.

2. Background of the Invention

The number of cars in cities continues to grow, placing an ever-increasing demand on a limited infrastructure of parking and roads. However, many of these cars are actually in use only a very small fraction of the time. Many drivers commute without a car by walking, bicycling or by public transportation, and their cars sit idle most of the week. Still others may commute by car, though alternative means of transportation are available, primarily because they anticipate a possible need for the car during the workday. These cars simply make traffic worse and needlessly occupy a valuable parking spot most workdays.

Shared-use systems have been described in the prior art, however, current systems are inconvenient for the vehicle drivers. Using a shared vehicle must be as convenient as possible or drivers will choose to use private vehicles instead. The shared vehicles should be located a short walk from a driver's home or work which means that they should be distributed over a wide area rather than centrally located or located in a small number of pods. Transaction

time and the number of steps that are required to gain entry to the vehicle should be minimized. Unnecessary steps such as retrieving a key from a kiosk, negotiating a barrier intended to secure the vehicle, filling out forms, etc. should be minimized. In addition, in current systems, the vehicles are frequently not
5 reliably available. A reservation system can enable efficient use of vehicles and helps ensure availability. The reservation system should enable a user to easily select an available vehicle and time, or allow the user to choose from alternatives that are similar to the desired vehicle and time. Access to vehicles should be secure from unauthorized users. During a reservation, access should
10 be restricted to the reserving driver. This provides an expected level of security for the reserving driver and prevents a vehicle from being used without a reservation either maliciously or inadvertently.

Several systems have been described for shared access or shared-use vehicles. Generally these systems describe various methods of access and
15 monitoring vehicles and are not integrated with a reservation system. As such, they provide ways of sharing vehicles that are less economical and/or less reliable than the present invention. Nor are they very scalable, many requiring specialized parking facilities, communication pods, or kiosks.

U.S. Patent Nos. 3,624,608 and 3,665,397 describe systems that do not
20 restrict access to the vehicles or include any reservation system. These systems require specially-modified stations to effect data transfer to and from the in-vehicle systems at each parking location and specially-modified parking locations for vehicle security. The systems do not provide for a high degree of security or reliability, nor is such a system easily scaled due to the infrastructure
25 required at each parking location.

U.S. Patent Nos. 5,519,260, 5,660,246 and 5,715,905 describe systems that are primarily concerned with vehicle monitoring and security. These systems do not include a reservation system.

There are a number of systems that require a single parking area, or
 5 multiple parking locations, to have a certain amount of infrastructure. Examples of these systems are described in U.S. Patent Nos. 5,812,070, 5,206,643, 5,726,885 and 5,066,853.

U.S. Patent No. 5,289,369 discloses a system that does not require any infrastructure modifications to the parking locations, but because the cars are
 10 parked in random locations, the system cannot guarantee the availability of a desired vehicle. According to this system, round trips are not required, which can result in an uneven distribution of vehicles, which then need to be redistributed.

It is therefore an object of the present invention to provide a system that
 15 allows a number of shared-use vehicles to be used by a number of drivers.

It is also an object to provide a system and method to access and monitor a vehicle-sharing system with an integrated reservation system.

It is a further object of the invention to provide a shared-use vehicle system that is convenient for use by the driver.

20 It is an additional object to provide a system that makes construction, management, and growth of a shared-use vehicle system economical.

Summary of the Invention

These and other objects are attained by the invention, which comprises a method and system for sharing the use of one or more vehicles by a plurality of
5 drivers.

According to the present invention, a system for controlling access to a vehicle is provided. The system includes a vehicle-associated access control module that is located in the vehicle. This module allows access to the vehicle by users who have been authorized
10 by a verification module. The verification module communicates with the vehicle-associated access control module over a communications such as the Internet or a wireless communications system.

The verification module includes a server that stores personal identification information for all authorized users, and vehicle information. The
15 server has a database that stores all reservation requests, including specific vehicles, dates and times, and authorizations.

An authorized user can thus make a reservation for a specific vehicle at a certain date and time, and can request a pick-up and drop-off location. At the appointed time, the user accesses the vehicle and presents identification such as
20 a smart card or PIN to gain access to the car. The system maintains all necessary information such as mileage, length of use, distance, and other such information, and when the user returns the car, automatically generates a bill.

Those skilled in the art will appreciate that the methods, systems and software products described herein can be implemented in systems and software

other than the specific examples set forth herein, and such examples are provided by way of illustration rather than limitation.

This specification, including the drawings attached hereto, will next present the invention at various levels of enabling detail, from conceptual to
5 specific examples of implementation.

FOR 201304260

Brief Description of the Drawings

5 Fig. 1 illustrates one embodiment of the vehicle access control system of the present invention.

 Fig. 2 shows an overview of the system.

10 Fig. 3 shows the system from the point of view of a driver using the system.

 Fig. 4 shows Step A of Fig. 3 in more detail.

15 Fig. 5 shows Step B of Fig. 3 in more detail.

 Fig. 6 shows Step C of Fig. 3 in more detail.

20 Fig. 7 shows Step D of Fig. 3 in more detail.

 Fig. 8 illustrates the overall system according to the preferred embodiment.

25 Fig. 9 shows an alternate embodiment of the system.

 Fig. 10 shows the vehicle-associated access control module system in more detail.

33222
 33223
 33224
 33225
 33226
 33227
 33228
 33229
 33230
 33231
 33232
 33233
 33234
 33235
 33236
 33237
 33238
 33239
 33240
 33241
 33242
 33243
 33244
 33245
 33246
 33247
 33248
 33249
 33250
 33251
 33252
 33253
 33254
 33255
 33256
 33257
 33258
 33259
 33260
 33261
 33262
 33263
 33264
 33265
 33266
 33267
 33268
 33269
 33270
 33271
 33272
 33273
 33274
 33275
 33276
 33277
 33278
 33279
 33280
 33281
 33282
 33283
 33284
 33285
 33286
 33287
 33288
 33289
 33290
 33291
 33292
 33293
 33294
 33295
 33296
 33297
 33298
 33299
 33300
 33301
 33302
 33303
 33304
 33305
 33306
 33307
 33308
 33309
 33310
 33311
 33312
 33313
 33314
 33315
 33316
 33317
 33318
 33319
 33320
 33321
 33322
 33323
 33324
 33325
 33326
 33327
 33328
 33329
 33330
 33331
 33332
 33333
 33334
 33335
 33336
 33337
 33338
 33339
 33340
 33341
 33342
 33343
 33344
 33345
 33346
 33347
 33348
 33349
 33350
 33351
 33352
 33353
 33354
 33355
 33356
 33357
 33358
 33359
 33360
 33361
 33362
 33363
 33364
 33365
 33366
 33367
 33368
 33369
 33370
 33371
 33372
 33373
 33374
 33375
 33376
 33377
 33378
 33379
 33380
 33381
 33382
 33383
 33384
 33385
 33386
 33387
 33388
 33389
 33390
 33391
 33392
 33393
 33394
 33395
 33396
 33397
 33398
 33399
 33400
 33401
 33402
 33403
 33404
 33405
 33406
 33407
 33408
 33409
 33410
 33411
 33412
 33413
 33414
 33415
 33416
 33417
 33418
 33419
 33420
 33421
 33422
 33423
 33424
 33425
 33426
 33427
 33428
 33429
 33430
 33431
 33432
 33433
 33434
 33435
 33436
 33437
 33438
 33439
 33440
 33441
 33442
 33443
 33444
 33445
 33446
 33447
 33448
 33449
 33450
 33451
 33452
 33453
 33454
 33455
 33456
 33457
 33458
 33459
 33460
 33461
 33462
 33463
 33464
 33465
 33466
 33467
 33468
 33469
 33470
 33471
 33472
 33473
 33474
 33475
 33476
 33477
 33478
 33479
 33480
 33481
 33482
 33483
 33484
 33485
 33486
 33487
 33488
 33489
 33490
 33491
 33492
 33493
 33494
 33495
 33496
 33497
 33498
 33499
 33500
 33501
 33502
 33503
 33504
 33505
 33506
 33507
 33508
 33509
 33510
 33511
 33512
 33513
 33514
 33515
 33516
 33517
 33518
 33519
 33520
 33521
 33522
 33523
 33524
 33525
 33526
 33527
 33528
 33529
 33530
 33531
 33532
 33533
 33534
 33535
 33536
 33537
 33538
 33539
 33540
 33541
 33542
 33543
 33544
 33545
 33546
 33547
 33548
 33549
 33550
 33551
 33552
 33553
 33554
 33555
 33556
 33557
 33558
 33559
 33560
 33561
 33562
 33563
 33564
 33565
 33566
 33567
 33568
 33569
 33570
 33571
 33572
 33573
 33574
 33575
 33576
 33577
 33578
 33579
 33580
 33581
 33582
 33583
 33584
 33585
 33586
 33587
 33588
 33589
 33590
 33591
 33592
 33593
 33594
 33595
 33596
 33597
 33598
 33599
 33600
 33601
 33602
 33603
 33604
 33605
 33606
 33607
 33608
 33609
 33610
 33611
 33612
 33613
 33614
 33615
 33616
 33617
 33618
 33619
 33620
 33621
 33622
 33623
 33624
 33625
 33626
 33627
 33628
 33629
 33630
 3

The invention is a system and method of sharing a car, or a fleet of cars, using a resource management reservation system. Each car is outfitted with a vehicle-associated access control module as described below. The main features of the system are the convenient and reliable access to shared vehicles via a reservation system, a means of identifying an authorized driver, a means for allowing or denying entry to, and use of a vehicle, and a means for monitoring vehicle use.

8

denying access to the vehicle. The invention may also be used to enable a specific group of drivers to share access to several vehicles, such as a corporate fleet of cars or trucks. In this case, the reservation and access mechanism would limit access to the corporate fleet to
5 drivers authorized by the corporation.

Each driver has a unique identifier. The unique identifier may be implemented in the system by a variety of means, including a password or a personal identification number. In the preferred embodiment, a personal identification number assigned to each driver allows secure access to the
10 reservation system of the present invention. The unique identifier may also include a smart card or chip card. In the preferred embodiment, a smart card is used to gain access to a vehicle.

Each of the cars in the fleet is parked in a specific location for a specific amount of time when not in use. A central resource management reservation
15 system stores data and determines when and where each vehicle is parked when not in use, allowing each driver to reliably reserve a specific vehicle for a specific duration.

Each of the cars in the fleet is equipped with a vehicle-associated access control module that has a means of communicating with the central resource
20 management reservation system. The vehicle-associated access control module is also equipped with a means of recognizing the identity of each driver by using a chip card reader, in the preferred embodiment.

Because most wireless communication mechanisms are not available
100 % of the time due to poor coverage, environmental shielding effects, or
25 other unforeseen conditions, the vehicle-associated access control module is intended to perform with partial availability of the communications link.

According to the preferred embodiment, a driver wishing to use one of the cars must first make a reservation. The driver may request a specific car in a specific location or one of a pool of cars in a specific location starting and ending at specific times. When the driver makes a reservation, the system checks the status of that particular driver and, if a problem exists with that user's account, notifies the user before continuing with the reservation process. If a requested vehicle or pickup location is not available, the system presents the user with alternate choices for the requested date and time.

If the requested car is available, or if there is adequate availability within the pool of cars, then the reservation is confirmed. Before the start of the reservation, the central resource management reservation system informs the appropriate vehicle-associated access control module of the details of the reservation including the chip card ID of the driver and the start and end time of the reservation.

At the time of the start of the reservation, the driver goes to the specific location and identifies himself by placing the proximity or chip card near the reader. If his ID matches the stored ID, then the vehicle-associated access control module unlocks the car door, disables the vehicle security system, enables ignition, and informs the server. The proximity or chip card is used to lock the car the same way it was used to unlock the car. During the reservation period and beyond, until a different proximity or chip card ID is detected, the vehicle-associated access control module permits the driver's proximity or chip card to be used to unlock and lock the car. At the end of the reservation, the vehicle-associated access control module informs the server of the vehicle usage time and distance traveled. This information permits the server to automatically calculate usage charges and to bill the driver's account accordingly. Because

the usage information is tracked automatically, the server can better manage the fleet of vehicles.

5 The vehicle-associated access control module monitors the status of the wireless communications link to the server. If there is ever a problem with the server, or with the communications link to the server, then the access control module does not trust any reservations it might know about and it allows any valid proximity or chip card ID to gain access and use the vehicle. Usage is monitored, and when the link to the server is re-established, the usage information is sent to the server. Reservation information is also sent from the server to the access control module. If the access control module determines that the current driver is using vehicle without a valid reservation, the access control module can sound an alarm alerting the driver.

15 The vehicle-associated access control module can accept new instructions via the wireless communications link to the server. This permits each of these modules to be updated remotely rather than requiring a visit to each of the vehicles every time a modification needs to be made.

The vehicle security system can be overridden for maintenance purposes, either by remote control or by special master IDs of the proximity or chip cards.

20 Nearly all of the components used in the system are conventional ones and need no detailed description. As stated above, the main feature of the present invention is the convenient and reliable access to shared vehicles.

25 The system provides for automated monitoring and tracking of vehicle use. If fees are charged for the use of the shared vehicles, bills are generated automatically from tracking data and submitted for automatic payment.

control module and the remote verification module communicate over a communications channel. These components and the overall system are described in more detail below, and in conjunction with the Figures.

Figure 1 illustrates one embodiment of the vehicle-associated access control system. The chip card reader 105, a Philips MIFARE Card Reader, detects a chip card and signals the Board Computer 101. The Board Computer 101 first determines whether or not the communication link to the Zipcar.com server (shown in Figure 2) via GSM-GPRS wireless modem 102 and Antenna 103 is enabled. If the communication link is enabled, the reservation data stored on the board computer are trusted and the board computer compares the ID of the proximity or chip card presented with the ID in each stored reservation. If the ID matches an appropriate reservation, the board computer unlocks the car door via the door locks module 107 and enables the ignition via the starter module 106. The display and keypad 108 can be used for further driver verification by requesting a driver-specific code be entered and compared before enabling the ignition. The display and keypad 108 can further be used to solicit information from the driver regarding the status of the vehicle and reservation. The display and keypad 108 can also be used to enable the driver to change the current reservation. The display and keypad 108 can also be used to create a new reservation if there is not one for this vehicle already. During use, Board Computer 101 monitors the Odometer 104. The total distance that was traveled during the reservation is stored for later transmission to the Zipcar.com server via GSM-GPRS 102 and Antenna 103. The system may also include a Global Position System (GPS) that allows the system to determine the location of each of the cars, both when in use and when not in use.

Figure 2 illustrates one embodiment of the overall system. The vehicle-associated access control system is contained in a plurality of cars 201 that communicate via wireless link through a base station 202 and a service provider 203 that is a gateway to the Internet 208. Typically, base station 202 and service provider 203 are components in a network provided by a wireless data service provider such as Verizon or Omnipoint or AT&T. The client PCs 209, 210, and 211 are used to access the Zipcar.com server 215 via the Internet 208 so that vehicle availability can be reviewed and reservations created. The accounting office 214 is also connected to the Internet allowing accountants to review the system activity and charges. Drivers can also review their own account status via their own PC (represented by PCs 209, 210, and 211) by accessing the Zipcar.com server 215 though the Internet 208. The Bank 213 is a payment processor that permits the Zipcar.com server 215 to automatically charge for usage of the cars and other fees via the Credit/Debit service module 207 in the Zipcar.com server 215. The Zipcar.com server 215 contains a database 204 that stores all the information necessary to manage the resource management reservation system. Web pages 205 are constructed by the Zipcar.com server 215 using information from the database 204 and can be displayed on the client PCs 208, 209, 210 via the Internet 208. The Zipcar.com server 215 can also send and receive email via the Email In/Out module 6 via the Internet 208. The corporate LAN 212 is connected to the Zipcar.com server 215 via a secure link allowing office personnel to manage the server.

Figure 3 describes the system from the point of view of the driver who wants to use a vehicle. As shown in Step A, the driver makes a reservation for a specific vehicle or one of a pool of vehicles parked in a specific location for a specific period of time. In Step B the driver goes to the specific location and gains access to the vehicle or one of a pool of vehicles using their proximity or

chip card and uses the vehicle. In Step C the driver returns the vehicle to a specific location. In Step D the driver is billed automatically for their use of the vehicle.

Figure 4 describes the method to make a reservation (Step A of Figure 3) in more detail. The driver's identity is verified, as shown in step 401, by any of various means including entering a username and password. Once the driver identity is verified, the zipcar.com server checks the driver account, shown in step 402, to make sure the driver is permitted to charge usage on the account. If the account is not verified, the driver may rectify whatever the problem is, such as enter a new credit card number, as shown in step 403. Once the driver's account is processed and accepted, then the driver specifies the desired location, start date and time, end date and time, and other optional parameters, shown in step 404. Individual driver preferences are stored in a database and preferences include the preferred city, neighborhood, location, vehicle type, and other such information. The system examines the individual driver's preferences to facilitate the selection of the desired reservation parameters, as shown in step 404.

As shown in step 405, the zipcar.com server checks for any available vehicle or vehicles that match the preferences specified. If no vehicles are available that match the preferences, alternative choices are presented to the driver, as shown in step 406. These alternatives are displayed ordered by the most likely preferred choices first, and the least likely preferred choices last. For example, the most likely choices may be the available vehicles nearest to the preferred vehicle. In this case, the locations of all vehicles are known and a well-known formula may be used to calculate the distance from the preferred vehicle to the available vehicles.

After the vehicle availability is confirmed, or an alternative vehicle is chosen, shown in step 406, the driver confirms the reservation, shown in step 407. The confirmation step allows the driver to select from among several available vehicles that match the preferences. The driver is also able to estimate
 5 the cost of the reservation by entering anticipated usage.

After the reservation is confirmed, the zipcar.com server establishes communication with the appropriate vehicle-associated access control module. Once this communication is established, the server transfers the reservation information, shown in step 409, to the vehicle-associated access control module.

10 Figure 5 describes Step B of Figure 3 in more detail. In Figure 5, the driver goes to the specific location and gains access to the vehicle. The operations shown in Figure 5 are implemented by the vehicle-associated access control module. As shown in step 501 of Fig. 5, the driver first identifies himself to the system. In the preferred
 15 embodiment, the means of identification is a proximity card, which could be provided by Applied Wireless Identification Group, Inc. (AWID) model Prox-Linc CS or KT. In the preferred embodiment, the access control module is equipped with a detector, which could be AWID model SR2400-ZIP. According to the system, the vehicle-
 20 associated processor is in communication with a proximity card detector that enables access to the vehicle only when a validated proximity card is placed in proximity to the card detector. The vehicle-associated processor may include associated audio/visual display elements, such as a visual display or a speaker. In an alternate embodiment, the vehicle-
 25 associated processor may also include data entry elements the user accesses to enter authorization data, such as a keyboard or a touch-

screen, or other devices available to enter a user-associated personal identification number for validation.

As shown in step 512 of Figure 5, the access control module determines whether the doors are locked or not. If the doors are not locked, as shown in
5 step 513, the vehicle-associated access control module sends a signal that causes the doors to be locked and the ignition to be disabled. The access control module then returns to wait for another signal from the proximity card detector. If the doors are locked, as shown in step 502, the processor determines if a reservation has begun.

10 If a new reservation has begun, as shown in Step 503, the ID from the proximity card is compared with the card ID for the current reservation. If the card ID matches, as shown in step 504, the processor sends a signal to the door unlock mechanism and enables the ignition via the Ignition Disable. If the ID does not match, as shown in step 505, access is refused by keeping the doors
15 locked and the ignition remains disabled. If, as shown in step 502, the processor determines that a reservation has not begun, the status of the wireless connection via the wireless modem and antenna to the zipcar.com server is queried (step 506). If the connection is enabled, the reservation data stored in Board Computer 101 is trusted and the card ID from the proximity card is
20 compared with the stored reservations (step 507). If the card ID matches, the processor records the beginning of the vehicle usage for this reservation (step 508). The system then allows for vehicle usage, shown in step 504. If the card ID does not match, access is refused.

If the system determines that the wireless connection is down, a simpler
25 test of the card ID is performed. If the card ID is determined to be valid, the start of vehicle usage is logged as above. If the card ID is determined to be invalid, access is refused. The system may perform a further check to

determine if the card ID matches a list of master ID numbers permitted to access the vehicle at all times (shown at steps 503, 507, and 510). As shown in step 507, a driver may be permitted access to the vehicle without a reservation. If the vehicle-associated access control module is equipped with a keyboard, user interface processor, and display, the driver may create a new reservation by entering desired information via the on-board keyboard. In certain embodiments, a driver is permitted access to the vehicle without a pre-authorized ID. In such a case, the resource management reservation system performs an authorization before allowing vehicle use. Such an authorization could include a background driving record check for insurance purposes and a credit check to determine creditworthiness.

Figure 6 describes Step C of Figure 3 in more detail. Each time the processor determines via the on-board vehicle system that the vehicle has been turned off, it determines whether the reservation has ended. If the reservation has not ended, the system will continue to wait until the end of the reservation. If the processor determines that the reservation has ended, the status of the wireless connection is determined, as shown in step 603. If the wireless connection is not enabled, the system will wait until the connection is established (shown in step 602). If the connection is enabled, the processor sends the vehicle usage details, such as the start of usage, the end of usage, the card ID of the user, and the vehicle status to the zipcar.com server.

Figure 7 describes Step D of Figure 3 in more detail. As shown in step 701, the zipcar.com server receives usage information from the vehicle-associated access control module. As shown in step 702, charges for a particular use of the vehicle may be calculated based on a number of factors including which vehicle was used, from which parking location, for how long and at what time of day, the distance driven, which driver, and other system-set

parameters. As shown in step 703, the charges are automatically submitted for payment.

Figure 8 shows the components of the overall system. The zipcar.com server 801 is connected to a database 802 that stores all the necessary
5 information to manage the resource management reservation system. The zipcar.com server 801 is connected to the Internet 803 that allows a plurality of browsers 805, also connected to the Internet 803, to be used by the system of the present invention to reserve vehicles, view vehicle availability, review account status, report problems with vehicles, and perform other functions. A
10 plurality of vehicle-associated access control modules 805 are also connected to the Internet 803 via a wireless link enabling communication between the on-board vehicle-associated access control modules 805 and the zipcar.com server 801.

When an authorized user, or driver, requests a reservation for a
15 car, the system accesses the database 802 and registers in the database 802, a reservation information item that represents the identity of the authorized user, the identity of the requested vehicle or vehicles, and the time requested by the reservation. When the system subsequently accepts, from a vehicle-associated processor 805, a request-to-access
20 message indicating that the user is at a vehicle and is requesting access to the vehicle, the system responds by verifying the access request. The system, to perform verification, first determines the identity of the user requesting access to the vehicle. The system then compares the identity of the user requesting access to the vehicle, the identity of the vehicle,
25 and the time of the request for access, against information contained in the reservation information item in the database. If the user requesting access is the user registered in the database and the vehicle is one of the

vehicles registered in the database, and the time of the request is also registered in the database, the system enables the user to access the vehicle.

Figure 9 is an alternate embodiment of the system for shared use of a vehicle according to the present invention. In some cases, the wireless link to the vehicle-associated access control modules 905 may not be via the Internet 903, but the connection may also be through some other network 906. This may be the case with the GSM network. The overall system and the other components are similar to that shown in Figure 8.

Figure 10 shows the vehicle-associated access control modules system in more detail. As shown in Figure 10, the processor 1001 monitors vehicle systems 1004, and determines various vehicle-specific facts, including whether the engine is running or not, the odometer reading, the battery voltage level, and other vehicle-specific facts. The processor 1001 also monitors an on-board GPS system and maintains the current location of the vehicle. The processor 1001 also monitors the proximity or chip card detector 1005. The processor 1001 is able to communicate with the zipcar.com Server via the wireless modem 1002, which in this example is a CDPD modem, Novatel Wireless Expedite model and antenna 1003. The proximity or chip card 1013 is used to identify the driver and is detected by the proximity chip card detector 1005. Processor 1001 is able to enable and disable the vehicle ignition via ignition disable 1009. Processor 1001 is able to lock the doors via door lock 1010. Processor 1001 is able to unlock the doors via door unlock 1011. Processor 1001 is able to sound an alarm via speaker 1012. A user interface processor 1007 may be optionally connected to processor 1001. This permits driver to enter data via keyboard 1006 or other input device. This also permits the display of information to the driver via display 1008.